




Grader Bits

Part Number	Insert	Washer	Fastening System	Shank Size	Head Diameter	Height	Ideal Board	Optional Board
C855HD	Blunt	-	Sleeve	0.88"	1.30"	2.84"	2000	2100, 2200, 5100
C855HDX	Blunt	-	Sleeve	0.88"	1.38"	2.88"		
C855HDX-4	Blunt	-	Sleeve	0.88"	1.38"	2.79"		
C855LR	Sharp	-	Sleeve	0.88"	1.38"	2.95"		
C855KCSB	Large	-	Sleeve	0.88"	1.38"	3.15"	2100	2200, 5100
C858KCSB	Large	-	Sleeve	0.88"	1.45"	3.39"		
C87DSSR	Sharp	-	Barbed Ring	0.88"	1.46"	3.58"	2100	5100
C87KCSBSR	Large	-	Barbed Ring	0.88"	1.56"	3.38"		
C387BF	Sharp	Yes	Sleeve	0.88"	1.50" (W1.70)	3.40"	2200	5100
C87HDRP	Blunt	Yes	Sleeve	0.88"	1.38" (W1.73)	3.31"		
C87WFRKCSB	Large	Yes	Sleeve	0.88"	1.50" (W1.73)	3.31"		
AR15087	Flat	-	Non-rotating	0.88"	1.58"	4.11"	5100	-
C1002443SB	Mining	-	Sleeve	1.00"	1.65"	4.00"	2500	2600
GH23NGT	Mining	Yes	Sleeve	1.00"	1.65" (W1.65)	4.00"		



Board Systems

Part Number	Shank size	Fastening System	Bit Spacing	Bits/3 ft board	Bits 4/ft board
2000	0.88"	Sleeve	1.50"	24	32
2100	0.88"	Sleeve/Ring	1.71"	21	28
2200	0.88"	Sleeve/Ring	2.00"	18	24
5100	0.88"	Sleeve/Ring	2.00"	18	24
2500	1.00"	Sleeve	1.71"	21	28
2600	1.00"	Sleeve	2.00"	18	24

Board Systems are punched for 3/4" Plow Bolts. Reducer bolts are available to adapt to 5/8" holes. Board Systems punched for 5/8" Plow Bolts are available with longer lead times.

510.0220

GRADER





BLACK CAT

WEAR PARTS




Sharp



Penetration



Standard



Wide

Non-Rotating Bits

Part Number	Description	Weight
1055183	Sharp	2.05 lbs
1055180	Penetration	2.36 lbs
6Y4339	Standard	2.54 lbs
6Y4340	Wide	3.94 lbs

Sharp Bits

50% narrower than the standard bit - 15.5mm wide. Allows larger aggregate to flow through.

Penetration Bits

Narrower than standard bit - 23mm wide
Wider gap allows larger aggregate to flow through.

Mix and Match


Alternate different bits to control the size of the material left behind.
Use wide bits on the end of the moldboard to prevent excessive wear.

Standard Bits

Baseline Bit - 30mm wide.
Moderate penetration.

Wide Bits

Can configure as a continuous edge.
Twice as wide as the standard bit - 60mm.



Board Systems

Part Number	Bolt Diameter	Length	Bit Spacing	# of Bits
1590311	0.625"	36"	Narrow	15
1590312	0.625"	48"	Narrow	20
1590315	0.625"	36"	Wide	12
1590316	0.625"	48"	Wide	16
1590318	0.750"	36"	Narrow	15
1590317	0.750"	48"	Narrow	20
1590313	0.750"	36"	Wide	12
1590314	0.750"	48"	Wide	16

510.0220

GRADER



www.blackcatwearparts.com sales@blackcatwearparts.com Toll Free: 1.800.661.6666 T: 780.465.6666 F: 780.465.9595

Caterpillar® and other identities and/or trademarks referred to in this publication are the registered marks of the entities noted herein. The use of any trademarks of others than Black Cat Blades Ltd. are solely and exclusively for identification, informational, comparative, and descriptive purposes. Black Cat Blades Ltd. is not affiliated with any owner of such registered marks and does not make, use, or sell any products manufactured by any such entity identified in this publication.